

Electrolytes

Advanced SOFC Powders



fuelcellmaterials.com
PERFORMANCE AND QUALITY DELIVERED

High Purity
Increased Performance
World Class Characterization

The electrolyte material is critical in both electrolyte and anode supported fuel cells. Electrolyte powder can be turned into supports, used as a barrier layer or added to electrode layers to improve performance. **fuelcellmaterials** offers many different formulations and surface area ranges to meet our customers' needs.

Nanoscale Electrolyte Powders

Truly nanocrystalline materials with 5 to 10 nanometer particles. Nano grade powders offer tremendous amounts of active surface area to extend triple phase boundaries and lower processing temperatures.

Ceramic Grade Ceria Powders

Specific grades of gadolinium or

samarium doped ceria powders are available for multiple cell structure applications. Tape cast grade powders are tailored for processes that require high slurry solids loadings, such as tape or slip casting. Mid grade powder is designed to provide excellent sinterability at lower processing temperatures. These powders are suitable for pellet pressing and other non-aqueous manufacturing processes.

Micron-Submicron Electrolyte Powders

fuelcellmaterials offers a broad selection of micron to submicron powders, including YSZ and LSGM. The wide variety of particle size ranges ensures there is a material available to meet all your needs.



R&D Focused Materials and Support

fuelcellmaterials tailors its business and products around the needs of researchers worldwide. All materials are offered in small quantities and are available to ship next day to ensure your research continues uninterrupted.

**Large variety of ceria based electrolyte powders
for multiple SOFC development applications.**

Tailored formulations and physical specifications to optimize performance


High purity and reproducibility

Ceria electrolytes with gadolinium or samarium dopants available


Submicron particle sizes to assist in lower processing temperatures

Scalable production to meet the needs of researchers and manufacturers


Particle Size Distribution




X-Ray Diffraction



Dilatometry



Electrical Conductivity



The values reported on this data sheet are to be considered typical and do not imply essential representation of the product specification. The information contained herein is believed to be accurate and reliable but is presented without guarantee or implied warranty of merchantability or fitness. Further, nothing presented herein should be interpreted as an authorization or inducement to infringe any relevant patent. Under no circumstances shall this company be liable for direct, incidental, consequential or other damages regardless of legal theory, arising out of the use or handling of the product or products referred to herein. The sole remedy of the buyer for any claims shall be limited to the buyer's purchase price. Technical advice is accepted at the buyer's risk and is not a warranty.



fuelcellmaterials.com

404 ENTERPRISE DRIVE P: 614-635-2025
 LEWIS CENTER, OH 43035 F: 614-842-6607

sales@fuelcellmaterials.com